Putoline Product recommendation

Husqvarna TC TC 250 (2007-2009)

ENGINE/TRANSMISSION
1,7 liter Capacity
0,2 liter Filter capacity

Recommended product: N-TECH® Pro R+ Off Road 10W-60, 10W-60
Normal, Change every 8 hours
First change only, Change every 3 hours

Good alternatives: Ester Tech Off Road 4+ 10W-60, 10W-60
Normal, Change every 8 hours
First change only, Change every 3 hours

HYDRAULIC BRAKE SYSTEM

Recommended product: Ultimate Racing Brake Fluid
Normal, Check every 4 hours
Normal, Change every 40 hours

Good alternatives: DOT 4 Brake Fluid
Normal, Check every 4 hours
Normal, Change every 40 hours

HYDRAULIC CLUTCH SYSTEM

Recommended product: Hydraulic Clutch Fluid

COOLING SYSTEM
1,1-1,3 liter Capacity

Recommended product: Ultracool 12
Normal, Check every 4 hours

Good alternatives: Coolant NF
Normal, Check every 4 hours

FRONT FORK
300-310 CM3 Capacity

Recommended product: HPX R 7.5W

SHOCK ABSORBER REAR

Recommended product: HPX R 2.5W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.