



## Putoline Product recommendation

### Husqvarna TE TE 450 (2010-2013)

#### ENGINE/TRANSMISSION

1,7 liter Capacity

0,2 liter Filter capacity

Recommended product N-TECH® Pro R+ Off Road 10W-50, 10W-50, 10W-50, 10W-50

Normal, Change every 5000 km

Initial service, Change every 1000 km

Competition, Change every 8 hours

Competition, first service only, Change every 3 hours

Good alternatives Ester Tech Off Road 4+ 10W-50, 10W-50, 10W-50, 10W-50

Normal, Change every 5000 km

Initial service, Change every 1000 km

Competition, Change every 8 hours

Competition, first service only, Change every 3 hours

#### HYDRAULIC BRAKE SYSTEM

Recommended product Ultimate Racing Brake Fluid,

Normal, Check every 5000 km

Competition, Check every 4 hours

Normal, Change every 10000 km

Competition, Change every 40 hours

Good alternatives DOT 4 Brake Fluid,

Normal, Check every 5000 km

Competition, Check every 4 hours

Normal, Change every 10000 km

Competition, Change every 40 hours

#### HYDRAULIC CLUTCH SYSTEM, BREMBO

Recommended product Ultimate Racing Brake Fluid,

Normal, Check every 5000 km

Competition, Check every 4 hours

Normal, Change every 10000 km

Competition, Change every 40 hours

Good alternatives DOT 4 Brake Fluid,

Normal, Check every 5000 km

Competition, Check every 4 hours

Normal, Change every 10000 km

Competition, Change every 40 hours

#### HYDRAULIC CLUTCH SYSTEM, MAGURA

Recommended product Formula GP 10W, 10W

Normal, Check every 5000 km

Competition, Check every 4 hours

Normal, Change every 10000 km

Competition, Change every 40 hours

Good alternatives HPX R 10W, 10W

Normal, Check every 5000 km

Competition, Check every 4 hours

Normal, Change every 10000 km

Competition, Change every 40 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

Good alternatives

#### **COOLING SYSTEM**

1,1-1,3 liter Capacity

Ultracool 12,

Normal, Check every 5000 km

Competition, Check every 4 hours

Coolant NF,

Normal, Check every 5000 km

Competition, Check every 4 hours

Recommended product

#### **FRONT FORK, KAYABA**

725 CM3 Capacity

Formula GP 5W

Recommended product

Good alternatives

#### **FRONT FORK, MARZOCCHI**

Formula GP 5W

HPX R 5W

Recommended product

Good alternatives

#### **SHOCK ABSORBER REAR**

Formula GP 5W

HPX R 5W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.