



Putoline Product recommendation

Kawasaki KX / KXF KX 125 KX125-L1 > L4 (1999-2002)

Recommended product	ENGINE <u>MX 7</u>
Good alternatives	<u>MX 5</u>
	TRANSMISSION, 6 0,7 liter Capacity
Recommended product	<u>N-TECH® Pro R+ 10W-30</u> Normal, Change every 3 races
Good alternatives	<u>Sport 4R 10W-30</u> Normal, Change every 3 races <u>N-TECH® Pro R+ Off Road 10W-40</u> Normal, Change every 3 races <u>Ester Tech Off Road 4+ 10W-40</u> Normal, Change every 3 races <u>Off Road 4 10W-40</u> Normal, Change every 3 races
Recommended product	HYDRAULIC BRAKE SYSTEM <u>Ultimate Racing Brake Fluid</u> Normal, Change every 24 months
Good alternatives	<u>DOT 4 Brake Fluid</u> Normal, Change every 24 months
Recommended product	GREASE POINTS/NIPPLES <u>White Action Grease + PTFE</u>
Good alternatives	<u>Racing Grease</u>
	COOLING SYSTEM 0,96 liter Capacity
Recommended product	<u>Ultracool 12</u> Normal, Check every 1 each race
Good alternatives	<u>Coolant NF</u> Normal, Check every 1 each race
	FRONT FORK 615-623 CM3 Capacity
Recommended product	<u>Formula GP 5W, 5W</u> Normal, Change every 5 races Initial service, Change every 2 races
Good alternatives	<u>HPX R 5W, 5W</u> Normal, Change every 5 races Initial service, Change every 2 races

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.