Putoline Product recommendation

KTM 350 350 EXC-F (2011-2012)

ENGINE/TRANSMISSION

1,2 liter Capacity

Recommended product
N-TECH® Pro R+ Off Road 10W-50, 10W-50
Normal, Change every 10 hours/ 70 liter consumed fuel
Initial service, Change every 1 hours/ 7 liter consumed fuel
Severe, Change every 10 hours/ 70 liter consumed fuel
Initial service, severe, Change every 1 hours/ 7 liter consumed fuel

Good alternatives
N-TECH® Pro R+ Off Road 10W-60, 10W-60
Normal, Change every 10 hours/ 70 liter consumed fuel
Initial service, Change every 1 hours/ 7 liter consumed fuel
Severe, Change every 10 hours/ 70 liter consumed fuel
Initial service, severe, Change every 1 hours/ 7 liter consumed fuel
Ester Tech Off Road 4+ 10W-50, 10W-50, 10W-60, 10W-60
Normal, Change every 10 hours/ 70 liter consumed fuel
Initial service, Change every 1 hours/ 7 liter consumed fuel
Severe, Change every 10 hours/ 70 liter consumed fuel
Initial service, severe, Change every 1 hours/ 7 liter consumed fuel

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product
Ultimate Racing Brake Fluid
Normal, Change every 12 months

Good alternatives
DOT 4 Brake Fluid
Normal, Change every 12 months
DOT 5.1 Brake Fluid
Normal, Change every 12 months

COOLING SYSTEM

1,2 liter Capacity

Recommended product
Ultracool 12

Good alternatives
Coolant NF

FRONT FORK

620 CM3 Capacity

Recommended product
Formula GP 5W

Good alternatives
HPX R 5W

SHOCK ABSORBER REAR

Recommended product
HPX R 2.5W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.