



Putoline Product recommendation

KTM 50 50 SX (2010-2012)

Recommended product	ENGINE, MHC <u>MX 9</u>
Good alternatives	<u>MX 7</u> <u>MX 5</u>
Recommended product	TRANSMISSION 0,2 liter Capacity <u>ATF</u> Normal, Change every 40 hours
Recommended product	HYDRAULIC BRAKE SYSTEM 0-0 liter Capacity <u>Ultimate Racing Brake Fluid</u> Normal, Change every 12 months
Good alternatives	<u>DOT 4 Brake Fluid</u> Normal, Change every 12 months <u>DOT 5.1 Brake Fluid</u> Normal, Change every 12 months
Recommended product	COOLING SYSTEM 0,5 liter Capacity <u>Ultracool 12</u>
Good alternatives	<u>Coolant NF</u>
Recommended product	FRONT FORK 210 CM3 Capacity <u>HPX R 7.5W</u>
Recommended product	SHOCK ABSORBER REAR <u>HPX R 2.5W</u>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.