

Good alternatives

Putoline Product recommendation

Aprilia RXV / SXV RXV / SXV 550 (2005-2017)

ENGINE

1,3 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-60, 10W-60, 10W-60, 10W-60

Normal, Change every 3000 km Severe, Change every 15 hours

First change only, Change every 500 km

Severe, first change only, Change every 3 hours

Good alternatives Ester Tech Off Road 4+ 10W-60, 10W-60, 10W-60, 10W-60

Normal, Change every 3000 km Severe, Change every 15 hours

First change only, Change every 500 km

Severe, first change only, Change every 3 hours

TRANSMISSION, 5

Recommended product N-TECH® Pro R+ Off Road 10W-60

Normal, Change every 3000 km <u>Ester Tech Off Road 4+ 10W-60</u> Normal, Change every 3000 km

HYDRAULIC BRAKE SYSTEM

Recommended product Ultimate Racing Brake Fluid, , , Normal, Check every 3000 km

Severe, Check every 15 hours

First change only, Check every 500 km

Severe, first change only, Check every 3 hours

Normal, Change every 12 months Severe, Change every 12 months

Good alternatives DOT 4 Brake Fluid, , ,

Normal, Check every 3000 km Severe, Check every 15 hours

First change only, Check every 500 km

Severe, first change only, Check every 3 hours

Normal, Change every 12 months Severe, Change every 12 months

COOLING SYSTEM

1,1 liter Capacity

Recommended product Ultracool 12, , ,

Normal, Check every 3000 km Severe, Check every 15 hours

First change only, Check every 500 km

Severe, first change only, Check every 3 hours

Good alternatives Coolant NF, , ,

Normal, Check every 3000 km Severe, Check every 15 hours

First change only, Check every 500 km

Severe, first change only, Check every 3 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

Good alternatives

FRONT FORK

Formula GP 10W, 10W Normal, Change every 9000 km Severe, Change every 45 hours HPX R 7.5W, 7.5W, 10W, 10W Normal, Change every 9000 km Severe, Change every 45 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.