Putoline Product recommendation

Baltmotors (RUS) ATV ATV 700 EFI

ENGINE/TRANSMISSION

1,9 liter Capacity
0,1 liter Filter capacity

Recommended product
N-TECH® Pro R+ Off Road 10W-50, 10W-50
Normal, Change every 1000 km/ 60 hours
Initial service, Change every 300 km/ 20 hours

Good alternatives
N-TECH® Pro R+ Off Road 15W-50, 15W-50
Normal, Change every 1000 km/ 60 hours
Initial service, Change every 300 km/ 20 hours
Ester Tech Quad RF4+ 10W-40, 10W-40
Normal, Change every 1000 km/ 60 hours
Initial service, Change every 300 km/ 20 hours
Quad RF4 10W-40, 10W-40
Normal, Change every 1000 km/ 60 hours
Initial service, Change every 300 km/ 20 hours

DIFFERENTIAL FRONT

0,33 liter Capacity

Recommended product
SP Gear Oil 75W-90, 75W-90
Normal, Check every 1000 km/ 60 months
Normal, Change every 5000 km/ 300 hours
Initial service, Change every 300 km/ 20 hours

Good alternatives
Heavy Gear 80W-90, 80W-90
Normal, Check every 1000 km/ 60 months
Normal, Change every 5000 km/ 300 hours
Initial service, Change every 300 km/ 20 hours

DIFFERENTIAL REAR

0,3 liter Capacity

Recommended product
SP Gear Oil 75W-90, 75W-90
Normal, Check every 1000 km/ 60 months
Normal, Change every 5000 km/ 300 hours
Initial service, Change every 300 km/ 20 hours

Good alternatives
Heavy Gear 80W-90, 80W-90
Normal, Check every 1000 km/ 60 months
Normal, Change every 5000 km/ 300 hours
Initial service, Change every 300 km/ 20 hours

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product
Ultimate Racing Brake Fluid,
Normal, Check every 1000 km/ 60 months
Initial service, Check every 300 km/ 20 hours

Good alternatives
DOT 4 Brake Fluid,
Normal, Check every 1000 km/ 60 months
Initial service, Check every 300 km/ 20 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.

COOLING SYSTEM
1,8 liter Capacity

Recommended product
Ultracool 12,
Normal, Check every 1000 km/ 60 months
Initial service, Check every 300 km/ 20 hours
Normal, Change every 24 months

Good alternatives
Coolant NF,
Normal, Check every 1000 km/ 60 months
Initial service, Check every 300 km/ 20 hours
Normal, Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.