



Putoline Product recommendation

Bimota Tesi Tesi 1D 906 (1991-1994)

Recommended product	ENGINE/TRANSMISSION
	4 liter Capacity
Good alternatives	<u>N-TECH® Pro R+ 10W-50, 10W-40</u> Normal, Change every 5000 km
	<u>Ester Tech 4+ 10W-40, 10W-50</u> Normal, Change every 5000 km
	<u>Sport 4R 10W-40, 15W-50</u> Normal, Change every 5000 km
	<u>Super DX4 10W-40</u> Normal, Change every 5000 km
Recommended product	HYDRAULIC BRAKE SYSTEM
	<u>Ultimate Racing Brake Fluid</u> Normal, Change every 20000 km/ 24 months
Good alternatives	<u>DOT 4 Brake Fluid</u> Normal, Change every 20000 km/ 24 months
Recommended product	COOLING SYSTEM
	2,9 liter Capacity
Good alternatives	<u>Ultracool 12</u> Normal, Change every 20000 km/ 24 months
	<u>Coolant NF</u> Normal, Change every 20000 km/ 24 months
Recommended product	FRONT FORK
	<u>Formula GP 10W</u> Normal, Change every 20000 km
Good alternatives	<u>HPX R 10W</u> Normal, Change every 20000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.