



Putoline Product recommendation

Gas Gas FSR FSR 450 (2008-2008)

ENGINE/TRANSMISSION	
Recommended product	1,2 liter Capacity
	<u>Boxer 4 15W-50, 15W-50</u>
Good alternatives	Normal, Change every 30 hours
	Initial service, Change every 5 hours
Good alternatives	<u>N-TECH® Pro R+ 10W-30, 10W-30</u>
	Normal, Change every 30 hours
Good alternatives	Initial service, Change every 5 hours
	<u>Sport 4R 10W-30, 10W-30</u>
Good alternatives	Normal, Change every 30 hours
	Initial service, Change every 5 hours
Good alternatives	<u>N-TECH® Pro R+ Off Road 10W-40, 10W-40, 15W-50, 15W-50</u>
	Normal, Change every 30 hours
Good alternatives	Initial service, Change every 5 hours
	<u>N-TECH® Pro R+ Off Road 10W-50, 10W-50</u>
Good alternatives	Normal, Change every 30 hours
	Initial service, Change every 5 hours
HYDRAULIC BRAKE SYSTEM	
Recommended product	0-0 liter Capacity
	<u>Ultimate Racing Brake Fluid</u>
Good alternatives	Normal, Change every 24 months
	<u>DOT 4 Brake Fluid</u>
Good alternatives	Normal, Change every 24 months
COOLING SYSTEM	
Recommended product	0-0 liter Capacity
	<u>Ultracool 12</u>
Good alternatives	Normal, Change every 24 months
	<u>Coolant NF</u>
Good alternatives	Normal, Change every 24 months
FRONT FORK	
Recommended product	
	<u>HPX R 7.5W</u>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.