



## Putoline Product recommendation

### Husaberg FE FE 450 (2009-2012)

#### ENGINE/TRANSMISSION

1,35 liter Capacity

Recommended product N-TECH® Pro R+ Off Road 10W-50, 10W-50, 10W-50

Normal, Change every 1 race/ 15 hours

Initial service, Change every 1 hours

Second change only, Change every 3 hours

Good alternatives Ester Tech Off Road 4+ 10W-50, 10W-50, 10W-50

Normal, Change every 1 race/ 15 hours

Initial service, Change every 1 hours

Second change only, Change every 3 hours

#### HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product Ultimate Racing Brake Fluid

Normal, Change every 12 months

Good alternatives DOT 4 Brake Fluid

Normal, Change every 12 months

DOT 5.1 Brake Fluid

Normal, Change every 12 months

#### HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product Hydraulic Clutch Fluid

Normal, Change every 12 months

#### COOLING SYSTEM

1 liter Capacity

Recommended product Ultracool 12

Normal, Check every 15 hours

Good alternatives Coolant NF

Normal, Check every 15 hours

#### FRONT FORK

Recommended product Formula GP 5W

Normal, Change every 12 months

Good alternatives HPX R 5W

Normal, Change every 12 months

#### SHOCK ABSORBER REAR

Recommended product HPX R 2.5W

Normal, Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.