



Putoline Product recommendation

Kawasaki KX / KXF KX 250 F KX250-T6F > T8F (2006-2008)

| | |
|-------------------------------|--|
| Recommended product | ENGINE/TRANSMISSION 1,5 liter Capacity <u>N-TECH® Pro R+ 10W-30</u> |
| | Normal, Change every 15 hours/ 6 races |
| Good alternatives | <u>Sport 4R 10W-30</u> |
| | Normal, Change every 15 hours/ 6 races |
| | <u>N-TECH® Pro R+ Off Road 10W-40</u> |
| | Normal, Change every 15 hours/ 6 races |
| | <u>N-TECH® Pro R+ Off Road 10W-50</u> |
| | Normal, Change every 15 hours/ 6 races |
| | <u>Ester Tech Off Road 4+ 10W-40, 10W-50</u> |
| | Normal, Change every 15 hours/ 6 races |
| HYDRAULIC BRAKE SYSTEM | |
| Recommended product | 0-0 liter Capacity <u>Ultimate Racing Brake Fluid</u> |
| | Normal, Change every 24 months |
| Good alternatives | <u>DOT 4 Brake Fluid</u> |
| | Normal, Change every 24 months |
| COOLING SYSTEM | |
| Recommended product | 1,2 liter Capacity <u>Ultracool 12</u> |
| | Normal, Check every 1 each race |
| Good alternatives | <u>Coolant NF</u> |
| | Normal, Check every 1 each race |
| FRONT FORK | |
| Recommended product | 322-417 CM3 Capacity <u>HPX R 4W</u> |
| | Normal, Change every 15 hours/ 6 races |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.