



Putoline Product recommendation

BMW K series K 1100 RS (1993-1996)

ENGINE

3,75 liter Capacity

0,25 liter Filter capacity

Recommended product N-TECH® Pro R+ 5W-40, 10W-40, 15W-50, 10W-30

Good alternatives

Normal, Change every 7500 km/ 6 months

Ester Tech 4+ 10W-40, 15W-50

Normal, Change every 7500 km/ 6 months

Sport 4R 10W-40, 15W-50, 10W-30

Normal, Change every 7500 km/ 6 months

Super DX4 10W-40

Normal, Change every 7500 km/ 6 months

SHAFT DRIVE

0,25 liter Capacity

Recommended product SP Gear Oil 75W-90

Good alternatives

Normal, Change every 15000 km/ 12 months

RS 75 75/80W

Normal, Change every 15000 km/ 12 months

Heavy Gear 80W-90

Normal, Change every 15000 km/ 12 months

TRANSMISSION, 5/1

0,8 liter Capacity

Recommended product SP Gear Oil 75W-90

Good alternatives

Normal, Change every 15000 km/ 12 months

RS 75 75/80W

Normal, Change every 15000 km/ 12 months

Heavy Gear 80W-90

Normal, Change every 15000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

0,5 liter Capacity

Recommended product Ultimate Racing Brake Fluid

Good alternatives

Normal, Check every 15000 km

Normal, Change every 12 months

DOT 4 Brake Fluid

Normal, Check every 15000 km

Normal, Change every 12 months

COOLING SYSTEM

3,4 liter Capacity

Recommended product Ultracool 12

Good alternatives

Normal, Change every 24 months

Coolant NF

Normal, Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

Good alternatives

FRONT FORK LEFT

0,35 liter Capacity

Formula GP 10W

Normal, Change every 15000 km/ 12 months

HPX R 10W

Normal, Change every 15000 km/ 12 months

FRONT FORK RIGHT

0,4 liter Capacity

Formula GP 10W

Normal, Change every 15000 km/ 12 months

HPX R 10W

Normal, Change every 15000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.