Putoline Product recommendation

# Ducati 1098 1098 R Bayliss (2009-2010)

## ENGINE/TRANSMISSION

3,7 liter Capacity

| | |
|---|---|
| Recommended product | N-TECH® Pro R+ 10W-40, 10W-40, 15W-50, 15W-50, 10W-30, 10W-30 |
| | Normal, Change every 12000 km/ 12 months |
| | Initial service, Change every 1000 km/ 6 months |
| Good alternatives | Ester Tech 4+ 10W-40, 10W-40 |
| | Normal, Change every 12000 km/ 12 months |
| | Initial service, Change every 1000 km/ 6 months |
| | Sport 4R 10W-40, 10W-40, 15W-50, 15W-50, 10W-30, 10W-30, 20W-50, 20W-50 |
| | Normal, Change every 12000 km/ 12 months |
| | Initial service, Change every 1000 km/ 6 months |

## HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

| | |
|---|---|
| Recommended product | Ultimate Racing Brake Fluid |
| | Normal, Change every 36000 km/ 36 months |
| Good alternatives | DOT 4 Brake Fluid |
| | Normal, Change every 36000 km/ 36 months |

## HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

| | |
|---|---|
| Recommended product | Ultimate Racing Brake Fluid |
| | Normal, Change every 36000 km/ 36 months |
| Good alternatives | DOT 4 Brake Fluid |
| | Normal, Change every 36000 km/ 36 months |

## GREASE POINTS/NIPPLES

| | |
|---|---|
| Recommended product | White Action Grease + PTFE |
| | Normal, Change every 12000 km/ 12 months |
| Good alternatives | Racing Grease |
| | Normal, Change every 12000 km/ 12 months |

## COOLING SYSTEM

2,3 liter Capacity

| | |
|---|---|
| Recommended product | Ultracool 12 |
| | Normal, Change every 36000 km/ 36 months |
| Good alternatives | Coolant NF |
| | Normal, Change every 36000 km/ 36 months |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

**KROON-OIL B.V.** Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.

**FRONT FORK**
155 mm Capacity

| | |
|---|---|
| Recommended product | ATF<br>Normal, Change every 36000 km/ 36 months |
| Good alternatives | Formula GP 5W<br>Normal, Change every 36000 km/ 36 months<br>HPX R 5W<br>Normal, Change every 36000 km/ 36 months |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

**KROON-OIL B.V.** Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.