Putoline Product recommendation

Ducati 848 Superbike 848 Superbike EVO Corse (2013-2013)

ENGINE/TRANSMISSION

3,7 liter Capacity

Recommended product
N-TECH® Pro R+ 10W-40, 10W-40, 15W-50, 15W-50, 10W-30, 10W-30
Normal, Change every 12000 km/ 12 months
Initial service, Change every 1000 km/ 6 months

Good alternatives
Ester Tech 4+ 10W-40, 10W-40, 15W-50, 15W-50
Normal, Change every 12000 km/ 12 months
Initial service, Change every 1000 km/ 6 months

Sport 4R 10W-40, 10W-40, 15W-50, 15W-50, 10W-30, 10W-30, 20W-50, 20W-50
Normal, Change every 12000 km/ 12 months
Initial service, Change every 1000 km/ 6 months

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product
Ultimate Racing Brake Fluid,
Normal, Check every 12000 km/ 12 months
Initial service, Check every 1000 km/ 6 months
Normal, Change every 36000 km/ 36 months

Good alternatives
DOT 4 Brake Fluid,
Normal, Check every 12000 km/ 12 months
Initial service, Check every 1000 km/ 6 months
Normal, Change every 36000 km/ 36 months

HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product
Ultimate Racing Brake Fluid,
Normal, Check every 12000 km/ 12 months
Initial service, Check every 1000 km/ 6 months
Normal, Change every 36000 km/ 36 months

Good alternatives
DOT 4 Brake Fluid,
Normal, Check every 12000 km/ 12 months
Initial service, Check every 1000 km/ 6 months
Normal, Change every 36000 km/ 36 months

COOLING SYSTEM

2,3 liter Capacity

Recommended product
Ultracool 12
Normal, Check every 12000 km/ 12 months
Normal, Change every 36000 km/ 36 months

Good alternatives
Coolant NF
Normal, Check every 12000 km/ 12 months
Normal, Change every 36000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.

FRONT FORK
439 CM3 Capacity

Recommended product	ATF
	Normal, Check every 12000 km/ 12 months
	Normal, Change every 36000 km/ 36 months
Good alternatives	Formula GP 5W
	Normal, Check every 12000 km/ 12 months
	Normal, Change every 36000 km/ 36 months
	HPX R 5W
	Normal, Check every 12000 km/ 12 months
	Normal, Change every 36000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.