



Putoline Product recommendation

Ducati Multistrada Multistrada 1200 S (2015-2015)

ENGINE/TRANSMISSION

4,1 liter Capacity

Recommended product

N-TECH® Pro R+ 10W-30, 10W-30

Normal, Change every 15000 km/ 12 months

Initial service, Change every 1000 km

Good alternatives

Sport 4R 10W-30, 10W-30

Normal, Change every 15000 km/ 12 months

Initial service, Change every 1000 km

N-TECH® Pro R+ Off Road 10W-40, 10W-40, 15W-50, 15W-50

Normal, Change every 15000 km/ 12 months

Initial service, Change every 1000 km

Ester Tech Off Road 4+ 10W-40, 10W-40, 15W-50, 15W-50

Normal, Change every 15000 km/ 12 months

Initial service, Change every 1000 km

HYDRAULIC BRAKE SYSTEM

0-0 liter Capacity

Recommended product

Ultimate Racing Brake Fluid

Normal, Check every 15000 km/ 12 months

Normal, Change every 36 months

Good alternatives

DOT 4 Brake Fluid

Normal, Check every 15000 km/ 12 months

Normal, Change every 36 months

HYDRAULIC CLUTCH SYSTEM

0-0 liter Capacity

Recommended product

Ultimate Racing Brake Fluid

Normal, Check every 15000 km/ 12 months

Normal, Change every 36 months

Good alternatives

DOT 4 Brake Fluid

Normal, Check every 15000 km/ 12 months

Normal, Change every 36 months

COOLING SYSTEM

2,5 liter Capacity

Recommended product

Ultracool 12

Normal, Check every 15000 km/ 12 months

Normal, Change every 60000 km/ 48 months

Good alternatives

Coolant NF

Normal, Check every 15000 km/ 12 months

Normal, Change every 60000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Recommended product

FRONT FORK, DSS

247-257 CM3 Capacity

HPX R 7.5W

Normal, Change every 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.