Putoline Product recommendation

Husqvarna TE TE 310 (2010-2012)

ENGINE/TRANSMISSION
0,9 liter Capacity
0,05 liter Filter capacity

Recommended product
N-TECH® Pro R+ Off Road 10W-50, 10W-50, 10W-50, 10W-50
Normal, Change every 5000 km
Initial service, Change every 1000 km
Competition, Change every 8 hours
Competition, first service only, Change every 3 hours

Good alternatives
Ester Tech Off Road 4+ 10W-50, 10W-50, 10W-50, 10W-50
Normal, Change every 5000 km
Initial service, Change every 1000 km
Competition, Change every 8 hours
Competition, first service only, Change every 3 hours

HYDRAULIC BRAKE SYSTEM

Recommended product
Ultimate Racing Brake Fluid,
Normal, Check every 5000 km
Competition, Check every 4 hours
Normal, Change every 10000 km
Competition, Change every 40 hours

Good alternatives
DOT 4 Brake Fluid,
Normal, Check every 5000 km
Competition, Check every 4 hours
Normal, Change every 10000 km
Competition, Change every 40 hours

HYDRAULIC CLUTCH SYSTEM, BREMBO

Recommended product
Ultimate Racing Brake Fluid,
Normal, Check every 5000 km
Competition, Check every 4 hours
Normal, Change every 10000 km
Competition, Change every 40 hours

Good alternatives
DOT 4 Brake Fluid,
Normal, Check every 5000 km
Competition, Check every 4 hours
Normal, Change every 10000 km
Competition, Change every 40 hours

HYDRAULIC CLUTCH SYSTEM, MAGURA

Recommended product
Formula GP 10W, 10W
Normal, Check every 5000 km
Competition, Check every 4 hours
Normal, Change every 10000 km
Competition, Change every 40 hours

Good alternatives
HPX R 10W, 10W
Normal, Check every 5000 km
Competition, Check every 4 hours
Normal, Change every 10000 km
Competition, Change every 40 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.

COOLING SYSTEM
0,9 liter Capacity

Recommended product	Ultracool 12, Normal, Check every 5000 km Competition, Check every 4 hours
Good alternatives	Coolant NF, Normal, Check every 5000 km Competition, Check every 4 hours

FRONT FORK, KAYABA
646 CM3 Capacity

Recommended product	Formula GP 5W

FRONT FORK, MARZOCCHI

Recommended product	Formula GP 5W
Good alternatives	HPX R 5W

SHOCK ABSORBER REAR

Recommended product	Formula GP 5W
Good alternatives	HPX R 5W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.