Putoline Product recommendation

KTM 450 450 EXC /-R (2008-2011)

ENGINE
0,6 liter Capacity

Recommended product	N-TECH® Pro R+ Off Road 10W-50, 10W-50
	Normal, Change every 100 liter consumed fuel/ 15 hours
	Initial service, Change every 3 hours/ 20 liter consumed fuel
Good alternatives	Ester Tech Off Road 4+ 10W-50, 10W-50
	Normal, Change every 100 liter consumed fuel/ 15 hours
	Initial service, Change every 3 hours/ 20 liter consumed fuel

TRANSMISSION, 6
0,9 liter Capacity

Recommended product	N-TECH® Pro R+ Off Road 15W-50, 15W-50
	Normal, Change every 100 liter consumed fuel/ 15 hours
	Initial service, Change every 3 hours/ 20 liter consumed fuel
Good alternatives	Ester Tech Off Road 4+ 15W-50, 15W-50
	Normal, Change every 100 liter consumed fuel/ 15 hours
	Initial service, Change every 3 hours/ 20 liter consumed fuel

HYDRAULIC BRAKE SYSTEM

Recommended product	DOT 5.1 Brake Fluid
	Normal, Change every 12 months

HYDRAULIC CLUTCH SYSTEM, BREMBO

Recommended product	DOT 5.1 Brake Fluid
	Normal, Check every 1 race/ 100 liter consumed fuel/ 15 hours
	Normal, Change every 12 months

HYDRAULIC CLUTCH SYSTEM, MAGURA
We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM
0,95 liter Capacity

Recommended product	Ultracool 12
	Normal, Check every 1 race/ 100 liter consumed fuel/ 15 hours
Good alternatives	Coolant NF
	Normal, Check every 1 race/ 100 liter consumed fuel/ 15 hours

FRONT FORK
626 CM3 Capacity

Recommended product	Formula GP 5W
	Normal, Change every 12 months
Good alternatives	HPX R 5W
	Normal, Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149, 7600 AC Almelo (Holland). Dollegoorweg 15, 7602 EC Almelo. Telefoon 0546-818165. Verkoop 0546-816184. Telefax 0546-817367.